



929DI EGT DUAL TRACK

REGULAR TRACK

NARROW TRACK

**30 HP
CATEGORY**



**JAPANESE TECHNOLOGY
DRIVEN DI ENGINE**



HIGH TORQUE



**DUAL ACTING
POWER STEERING**



**SUPERIOR STYLING WITH
GREAT ERGONOMICS**



**FRONT BONNET
WITH LOCK**



**MULTI-APPLICATIONS
SUITABILITY**



DUAL TRACK

1800 419 0136

info@vsttractors.com

www.vsttractors.com

VST 929DI EGT DUAL TRACK

TECHNICAL SPECIFICATION

9 CROP EXPERT



PADDY



GRAPES



MILLETS



POMEGRANATE



VEGETABLES



SUGARCANE



MAIZE



SOYABEAN



COTTON

AGGREGATES	PARAMETERS	VST 929 DI EGT DUAL TRACK
ENGINE	ENGINE TYPE	TREM IIIA, NATURALLY ASPIRATED 4 STROKE ENGINE
	HP (kW) CATEGORY	29 (21.62)
	NO. OF CYLINDERS	3
	RATED ENGINE SPEED	2800
	DISPLACEMENT (cc)	1331
	COOLING	WATER COOLED
	AIR CLEANER	DRY TYPE - DUAL FILTER
	TORQUE Kgm (Nm)	8.6 (84.3)
	PTO HP (kW)	24 (17.9)
TRANSMISSION	CLUTCH TYPE	SINGLE DRY FRICTION PLATE
	GEAR BOX TYPE	CONSTANT MESH
	NO. OF GEARS	8 FORWARD + 2 REVERSE
	SHIFTING PATTERN	SIDE SHIFT
	SPEED FORWARD (km/hr)	1.56 - 20.26
	SPEED REVERSE (km/hr)	1.39 - 5.05
	BRAKES	OIL IMMERSED BRAKES
	STEERING	POWER
	PTO	DUAL PTO
	PTO (MAXIMUM) SPEED	540, 540E
	POWER DRIVE	4 WHEEL DRIVE
FUEL TANK	CAPACITY (L)	24
HYDRAULICS	ADDC	AUTO DRAFT & DEPTH CONTROL
	THREE POINT HITCH	CATEGORY - 1
	LIFTING CAPACITY (kg)	750
TYRES SIZE	FRONT	6 X 12
	REAR	8.30 X 20
DIMENSIONS & CAPACITY	OVERALL LENGTH (mm)	2530
	OVERALL WIDTH (mm)	960 - 1095
	OVERALL HEIGHT (mm)	1323
	WHEEL BASE (mm)	1520
	GROUND CLEARANCE (mm)	325
	TURNING RADIUS (m)	2.1
	TOTAL WEIGHT (kg)	860 WITHOUT BALLAST



Trust of >7 lakh farmers.
Legacy of >50 years



No. 1 Power Tiller brand



Global footprints
in > 40 countries



Widest working range
(17 HP to 50 HP)



1st 4WD
compact Tractors



Year on Year Growth
Rate of over 20%



Regd. Office: Plot No- 1, Dyavasandra Indl. Layout, Whitefield Road, Mahadevapura Post, Bengaluru-560048, Karnataka. INDIA
Phone: +91-80-67141111, e-mail: info@vsttractors.com, CIN: L34101KA1967PLC001706. www.vsttractors.com

Disclaimer: Pictures used here are for illustration purpose only. Product specifications are subject to change without prior notice.
Performance of the machine may vary with user/field/working conditions

Authorised Dealer



1800 419 0136

f vsttillers

in vst-tillers

▶ VST Tillers Tractors Limited